

TANKLEAN

IMPORTANT

RINSE ALL EQUIPMENT WITH CLEAN WATER AFTER TREATING WITH TANKLEAN. DISPOSE OF RINSATE ACCORDING TO APPROVED LOCAL PRACTICES.

CAUTION: KEEP OUT OF REACH OF CHILDREN

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Follow proper procedures for the disposal of rinsate. Triple rinse and dispose of empty container according to approved local practices.

CONDITIONS OF SALE

Seller warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use. Weather, crop conditions, timing and methods of applications, mixtures with other chemicals not specifically recommended, and other influencing factors in the use of this product are beyond the control of the seller. Buyer assumes all risks of use, storage, or handing of this material not in strict accordance with directions given herewith.

Net Contents: 1 qt

Net Weight:

Lot Number:



Cleans stubborn residues from agricultural spray equipment

GENERAL INFORMATION

TANKLEAN is a multi-purpose cleaner designed for cleaning agricultural spray equipment and mix tanks, as well as a degreaser for engines and tools. TANKLEAN's versatility allows it to be used in all types of equipment as well as on the exterior of spray equipment and tanks. TANKLEAN is concentrated and is still effective when mixed in high dilution ratios.

RATE:

LARGE VOLUME SPRAYERS:

Use 1 ÷ 2 pints of TANKLEAN per 150 gallons of wash water. Rates of cleaner and water may be varied according to individual cleaning requirements.

Add TANKLEAN at recommended rates to the water in the tank for 5 minutes. Then agitate the solution for 10 minutes, ensuring that all parts of the sprayer are covered. For heavy residues, a longer soaking may be necessary.

To clean pesticide deposits, brush undiluted TANKLEAN directly on the stain and let stand for several minutes. Purge all hoses, lines, valves and nozzles for at least one minute after cleaning. Drain system completely and rinse all equipment parts with clean water.

HAND-HELD AND BACK PACK SPRAYERS:

Use 1 ounce of TANKLEAN for each gallon of wash water. Let solution stand for 5 minutes, then agitate and drain. Rinse all parts with clean water after draining.

All Ingredients are exempt from tolerance levels in CFR 40, 180.1001.

MANUFACTURED BY:
CUSTOM AG FORMULATORS, INC.
P.O. BOX 26104, FRESNO, CA 93729

SPECIMEN LABEL